

The DOE must propose its chosen method, and any underlying assumptions, to NRC for approval.

(1) DOE may calculate the dimensions as a well-capture zone. If DOE uses this approach, it must assume that the:

(i) Water supply well(s) has (have) characteristics consistent with public water supply wells in the Town of Amargosa Valley, Nevada, for example, well-bore size and length of the screened intervals;

(ii) Screened interval(s) include(s) the highest concentration in the plume of contamination in the accessible environment; and

(iii) Pumping rates and the placement of the well(s) must be set to produce an annual withdrawal equal to the representative volume and to tap the highest concentration within the plume of contamination.

(2) DOE may calculate the dimensions as a slice of the plume. If DOE uses this approach, it must:

(i) Propose, for approval, where the location of the edge of the plume of contamination occurs. For example, the place where the concentration of radionuclides reaches 0.1% of the level of the highest concentration in the accessible environment;

(ii) Assume that the slice of the plume is perpendicular to the prevalent direction of flow of the aquifer; and

(iii) Assume that the volume of ground water contained within the slice of the plume equals the representative volume.

ADDITIONAL PROVISIONS

§ 63.341 Projections of peak dose.

To complement the results of § 63.311, DOE must calculate the peak dose of the reasonably maximally exposed individual that would occur after 10,000 years following disposal but within the period of geologic stability. No regulatory standard applies to the results of this analysis; however, DOE must include the results and their bases in the environmental impact statement for Yucca Mountain as an indicator of long-term disposal system performance.

§ 63.342 Limits on performance assessments.

DOE's performance assessments should not include consideration of very unlikely features, events, or processes, i.e., those that are estimated to have less than one chance in 10,000 of occurring within 10,000 years of disposal. Unlikely features, events, and processes, or sequences of events and processes shall be excluded from the assessments for the human intrusion and ground water protection standards upon prior Commission approval for the probability limit used for unlikely features, events, and processes. In addition, DOE's performance assessments need not evaluate the impacts resulting from any features, events, and processes or sequences of events and processes with a higher chance of occurrence if the results of the performance assessments would not be changed significantly.

§ 63.343 Severability of individual protection and ground-water protection standards.

The individual protection and ground-water protection standards are severable.

PART 70—DOMESTIC LICENSING OF SPECIAL NUCLEAR MATERIAL

Subpart A—General Provisions

Sec.

70.1 Purpose.

70.2 Scope.

70.3 License requirements.

70.4 Definitions.

70.5 Communications.

70.6 Interpretations.

70.7 Employee protection.

70.8 Information collection requirements: OMB approval.

70.9 Completeness and accuracy of information.

70.10 Deliberate misconduct.

Subpart B—Exemptions

70.11 Persons using special nuclear material under certain Department of Energy and Nuclear Regulatory Commission contracts.

70.12 Carriers.

70.13 Department of Defense.

70.14 Foreign military aircraft.

70.17 Specific exemptions.